



Product Specification

Sheet

Centerfire Pistol & Revolver

LOAD NUMBER: P9CSP1

CALIBER: 9mm Luger +P

CASE: Nickel Plated Brass (Copper Alloy No. 260)

BULLET: 124 Gr. Expanding Full Metal Jacket

PRIMER: Federal No. 200

Primer Mix contains Basic Lead Styphnate.

Operating Range (-40 degrees to +125 degrees Fahrenheit).

PRIMER SEALANT: Water resistant anaerobic sealer

CASE MOUTH SEALANT: Water Resistant mouth varnish

HEADSTAMP: Each loaded cartridge shall be headstamped with the manufacturer's symbol and appropriate cartridge designation

ACCURACY: Three 5-round groups with maximum average extreme spread of 3.0" at 50 yards, using a Mann Rest Test System.

INSTRUMENTAL VELOCITY: 1140 +/- 40 FPS using a 4.00" SAAMI standard test barrel

MUZZLE ENERGY: 358 Ft-Lbs.

CHAMBER PRESSURE: Piezotronic maximum average per 10 rounds -38,500 PSI

BULLET PULL: Minimum individual 45 Lbs.

PROPELLANT DETECTION: 100% mechanical and/or electrical detection of propellant levels within the cartridge

VISUAL INSPECTION: 100% visual inspection of finished cartridges prior to packaging

LOT IDENTIFICATION: Each lot of ammunition is assigned a unique identification number to include the day, month and year of manufacture and assembly line on which manufactured

Federal Cartridge Company
900 Ehlen Drive
Anoka, MN 55303
(800)322-2342, ext. 3822 or 2370