



## Product Specification Sheet Centerfire Pistol & Revolver

**LOAD NUMBER:** AE9N1

**CALIBER:** 9mm Luger

**CASE:** Brass (Copper Alloy No 260)

**BULLET:** 124 Gr. TMJ Total Metal Jacket

**PRIMER:** Federal No. 205 TMF

Non Toxic Primer Mix

Operating Range (-40 degrees to +125 degrees Fahrenheit)

**PRIMER SEALANT:** Loctite Primer Sealant

**CASE MOUTH SEALANT:** Water Resistant

**CASE KNURL:** Yes

**HEADSTAMP:** Each loaded cartridge shall be headstamped with the manufacturer's symbol and appropriate cartridge designation.

**ACCURACY:** Three 5-round groups with maximum average extreme spread of 4.0" at 50 yards, using a Mann Rest Test System.

**INSTRUMENTAL VELOCITY:** 1090 +/- 50 FPS using a 4.00" SAAMI standard test barrel

**MUZZLE ENERGY:** 327 Ft-Lbs

**CHAMBER PRESSURE:** Piezotronic maximum average per 10 rounds – 35,000 PSI

**BULLET PULL:** Minimum individual 80 Lbs

**PROPELLANT DETECTION:** 100% mechanical and/or electrical detection of propellant levels within the cartridge

**VISUAL INSPECTION:** 100% visual inspection of finished cartridges prior to packaging

**LOT IDENTIFICATION:** Each lot of ammunition is assigned a unique identification number to include the day, month and year of manufacture and assembly line on which manufactured

**Federal Cartridge Company**  
900 Ehlen Drive  
Anoka, MN 55303  
(800)322-2342, ext. 3822 or 2370