



Product Specification Sheet

Federal Cartridge Company
900 Ehlen Drive
Anoka, MN 55303

LOAD NUMBER: AE9SJ2

CALIBER: 9mm Luger

CASE: Brass, Copper Alloy No 260

BULLET: 124 gr. Total Synthetic Jacket (TSJ)

PRIMER: Federal No. 200 Catalyst™ lead-free primer

PRIMER SEALANT: None

CASE MOUTH SEALANT: None

HEADSTAMP: Each loaded cartridge shall be headstamped with the manufacturer's symbol and appropriate cartridge designation.

ACCURACY: Three 5-round groups with maximum average extreme spread of 6.5 inch at 50 yards, using a Mann Rest Test System.

INSTRUMENTAL VELOCITY:

1075 ± 25 fps using a 4.00 inch SAAMI standard test barrel

MUZZLE ENERGY: 318 ft.-lbs.

CHAMBER PRESSURE: Piezotronic maximum average per 10 rounds = 35,000 psi

BULLET PULL: Minimum individual 45 lbs.

PROPELLANT DETECTION: 100% mechanical and/or electrical detection of propellant levels within the cartridge

VISUAL INSPECTION: 100% visual inspection of finished cartridges prior to packaging

LOT IDENTIFICATION: Each lot of ammunition is assigned a unique identification number to include the day, month and year of manufacture and assembly line on which manufactured