



Sheet

Product Specification

Centerfire Pistol & Revolver

LOAD NUMBER: AE9N2

CALIBER: 9 mm Luger

CASE: Brass (Copper Alloy No 260)

BULLET: 147 Gr. TMJ Total Metal Jacket

PRIMER: Federal No. 205NT

Non-Toxic Primer Mix

Operating Range (-40 degrees to +125 degrees Fahrenheit)

PRIMER SEALANT: Moisture & Organic Vapor Resistant Lacquer

CASE MOUTH SEALANT: Water Resistant

CASE KNURL: Yes

HEADSTAMP: Each loaded cartridge shall be headstamped with the manufacturer's symbol and appropriate cartridge designation.

ACCURACY: Three 5-round groups with maximum average extreme spread of 3.0" at 50 yards, using a Mann Rest Test System.

INSTRUMENTAL VELOCITY: 960 +/- 50 FPS using a 4.00" SAAMI standard test barrel

MUZZLE ENERGY: 300 Ft-Lbs

CHAMBER PRESSURE: Piezotronic maximum average per 10 rounds – 35,000 PSI

BULLET PULL: Minimum individual 80 Lbs

PROPELLANT DETECTION: 100% mechanical and/or electrical detection of propellant levels within the cartridge

VISUAL INSPECTION: 100% visual inspection of finished cartridges prior to packaging

LOT IDENTIFICATION: Each lot of ammunition is assigned a unique identification number to include the day, month and year of manufacture and assembly line on which manufactured

Federal Cartridge Company
900 Ehlen Drive
Anoka, MN 55303
(800)322-2342, ext. 3822 or 2370