



Product Specification Sheet Centerfire Rifle

LOAD NUMBER: GM338LM

CALIBER: .338 Lapua Magnum

CASE: Brass, Copper Alloy No. 260

BULLET: 250 gr. Sierra MatchKing

PRIMER: Federal GM216M

Primer mix contains Basic Lead Styphnate

OPERATING RANGE: -40° to 125° F

PRIMER SEALANT: Lacquer

CASE MOUTH SEALANT: None

HEADSTAMP: Each loaded cartridge head stamped with manufacturer symbol and caliber

ACCURACY: Three 5-round groups with maximum average extreme spread of 1.60 in. at 200 yards in a SAAMI standard test barrel

VELOCITY: 2875 ± 50 fps using a 24.00 in. SAAMI standard test barrel

MUZZLE ENERGY: 4588 ft.-lbs.

CHAMBER PRESSURE: 65,000 psi maximum average pressure

PROPELLANT DETECTION: 100% mechanical and/or electrical detection of propellant levels within the cartridge

VISUAL INSPECTION: 100% visual inspection of finished cartridges prior to packaging

LOT IDENTIFICATION: Each lot of ammunition is assigned a unique identification number to include the day, month and year of manufacture and assembly line on which manufactured.

PACKAGING: 20 rounds per carton, 10 cartons per case

Federal Cartridge Company
900 Ehlen Drive
Anoka, MN 55303
(800)322-2342, ext. 3822 or 2370