



**Product Specification Sheet**  
Federal Cartridge Company  
900 Ehlen Drive  
Anoka, MN 55303

**LOAD NUMBER:** GM65CRD1

**CALIBER:** 6.5mm Creedmoor

**CASE:** Brass (Copper Alloy No. 260)

**BULLET:** 140 Gr. Sierra Match King Boat-Tail  
Hollow Point

**PRIMER:** Federal No. GM205M Primer Mix  
contains Basic Lead Styphnate. Operating Range  
(-40° F to 125° F).

**PRIMER SEALANT:** Water Resistant  
Anaerobic Sealant

**CASE MOUTH SEALANT:** None

**CASE KNURL:** None

**HEADSTAMP:** Each loaded cartridge shall be  
headstamped with the manufacturer's symbol  
and appropriate cartridge designation

**ACCURACY:** Two 10-round groups with  
maximum average extreme spread of 1.7" at 200  
yards, using a Mann Rest Test System

**INSTRUMENTAL VELOCITY:** 2675 ± 50  
fps using a 24.00" SAAMI standard test barrel

**MUZZLE ENERGY:** 2,225 Ft-lbs.

**CHAMBER PRESSURE:** Piezotronic  
maximum average per 10 rounds – 62,000 psi

**BULLET PULL:** Minimum individual 40 lbs.

**PROPELLANT DETECTION:** 100%  
mechanical and/or electrical detection of  
propellant levels within the cartridge

**VISUAL INSPECTION:** 100% visual  
inspection of finished cartridges prior to  
packaging

**LOT IDENTIFICATION:** Each lot of  
ammunition is assigned a unique identification  
number to include the day, month and year of  
manufacture and assembly line on which  
manufactured.