



Product Specification Sheet

Federal Cartridge Company

900 Ehlen Drive

Anoka, MN 55303

LOAD NUMBER: LEB127 DPRS

CALIBER: 12 ga. 2 ¾"

SLUG: 1 oz. Foster Rifled Slug

SLUG DESCRIPTION: Copper Plated
Lead at 0.7% Antimony

PRIMER: Federal No. 202 sealed with
lacquer

DRAM EQUIVALENT: Max

TUBE: Blue Plastic

WADDING: Recoil wad & plastic
sphere

BASEWAD: Paper basewad

CRIMP: Roll crimp

CRIMP SEAL: No

HEAD: Brass

HEADSTAMP: Each loaded cartridge
shall be headstamped with the
manufacturer's symbol and appropriate
cartridge designation

EXTREME SPREAD: (TYPICAL):
4" E.S. at 50 yards in test barrel

INSTRUMENTAL VELOCITY:
1350 ± 50 fps at 3 feet from the muzzle
of a standard SAAMI test barrel

CHAMBER PRESSURE: 11500 psi
maximum average

PROPELLANT DETECTION: 100%
mechanical and/or electrical detection of
propellant levels within the cartridge

VISUAL INSPECTION: 100% visual
inspection of finished cartridges prior to
packaging

LOT IDENTIFICATION: Each lot of
ammunition is assigned a unique
identification number to include the day,
month and year of manufacture or
assembly line on which manufactured