



Product Specification Sheet Shotshell

LOAD NUMBER: LEF127 RS

CALIBER: 12 ga. 2 ¾"

SLUG: 1 oz Foster Rifled Slug

SLUG DESCRIPTION: Pure Lead

PRIMER: Federal No. 202 sealed with lacquer

DRAM EQUIVALENT: Max

TUBE: Blue HDPE Plastic

CHAMFERED TUBE: No

BASEWAD: 9/16" paper basewad

CRIMP: Roll crimp standard

CRIMP SEAL: No

HEAD: Brass

HEADSTAMP: Each loaded cartridge shall be headstamped with the manufacturer's symbol and appropriate cartridge designation

Federal Cartridge Company
900 Ehlen Drive
Anoka, MN 55303
(800)322-2342, ext. 3822 or 2370

PATTERN (TYPICAL): 5" E.S. at 50 yards in test barrel

INSTRUMENTAL VELOCITY:
1610 +/- 50 FPS at 3 feet from the muzzle of a standard SAAMI test barrel

CHAMBER PRESSURE: 11500 PSI maximum average

PROPELLANT DETECTION: 100% mechanical and/or electrical detection of propellant levels within the cartridge

VISUAL INSPECTION: 100% visual inspection of finished cartridges prior to packaging

LOT IDENTIFICATION: Each lot of ammunition is assigned a unique identification number to include the day, month and year of manufacture and assembly line on which manufactured