



## Product Specification Sheet Shotshell

**LOAD NUMBER:** H123 4

**CALIBER:** 12 Ga. 2 3/4"

**SHOT BUFFER:** None

**SHOT VOLUME:** 1-1/8 oz.

**SHOT DESCRIPTION:** Hard Shot

**PRIMER:** Federal No. 209a

**DRAM EQUIVALENT:** 3 1/4

**TUBE:** Red plastic

**CHAMFERED TUBE:** Yes

**BASEWAD:** 9/16" paper basewad

**CRIMP:** 8 segment standard

**CRIMP SEAL:** No

**PATTERN (ACCURACY):** 75% at 40 yards in 30" circle (full choke)

**INSTRUMENTAL VELOCITY:**  
1255 +/- 50 FPS at 3 feet from the muzzle of a standard SAAMI test barrel

**CHAMBER PRESSURE:** 11500 PSI maximum average

**PROPELLANT DETECTION:** 100% mechanical and/or electrical detection of propellant levels within the cartridge

**VISUAL INSPECTION:** 100% visual inspection of finished cartridges prior to packaging

**LOT IDENTIFICATION:** Each lot of ammunition is assigned a unique identification number to include the day, month and year of manufacture and assembly line on which manufactured

**Federal Cartridge Company**  
900 Ehlen Drive  
Anoka, MN 55303  
(800)322-2342, ext. 3822 or 2370