



**Product Specification Sheet**  
**Federal Cartridge Company**  
**900 Ehlen Drive**  
**Anoka, MN 55303**

**LOAD NUMBER:** LE127 00

**CALIBER:** 12 ga. 2 3/4"

**SHOT BUFFER:** Yes

**SHOT VOLUME:** 9 Pellets

**SHOT DESCRIPTION:** Copper  
Plated, 3% Antimony Lead

**WAD:** One-piece FLITECONTROL

**PRIMER:** Federal No. 202 sealed with  
lacquer

**TUBE:** Red HDPE

**CHAMFERED TUBE:** Yes

**BASEWAD:** Integral Basewad

**CRIMP:** 6 Segment

**CRIMP SEAL:** Yes

**HEAD:** Brass

**HEADSTAMP:** Each loaded cartridge shall be headstamped with the manufacturer's symbol and appropriate cartridge designation.

**PATTERN (TYPICAL):** 5 Round  
maximum average extreme spread of  
15" at 25 yards (IC choke)

**INSTRUMENTAL VELOCITY:**  
1325 ± 50 fps at 3 feet from the muzzle  
of a standard SAAMI test barrel

**CHAMBER PRESSURE:** 11500 psi  
maximum average

**PROPELLANT DETECTION:** 100%  
mechanical and/or electrical detection of  
propellant levels within the cartridge

**VISUAL INSPECTION:** 100% visual  
inspection of finished cartridges prior to  
packaging

**LOT IDENTIFICATION:** Each lot of  
ammunition is assigned a unique  
identification number to include the day,  
month and year of manufacture and  
assembly line on which manufactured