

SPEER[®] LE



Product Information Sheet

9mm 147gr Gold Dot G2
Service Ammunition

LOAD NUMBER: 54226

LOAD: 9mm Luger 147gr Gold Dot G2 (GDG2)

CASE: Nickel Plated Brass

BULLET: 147 grain Gold Dot G2

PRIMER: CCI #529

PRIMER SEALANT: Yes

MOUTH SEALANT: Yes

HEADSTAMP: SPEER 9mm Luger YOM

LOT IDENTIFICATION: Each lot of ammunition is assigned a unique identification number. This includes information on the day, month, and year of manufacture and assembly line on which the ammunition was manufactured. SEE PPS 24402 (A01A201 = Jan 01 2019 Line 2 Lot 01)

ACCURACY: 3 inches at 25 yds

INSTRUMENTAL VELOCITY: 990 ± 50fps using a 4" SAAMI standard test barrel.

MAXIMUM RANGE: 5,806 feet at 34°, impact velocity 276 fps

MUZZLE ENERGY: 320 Ft-lbs

CHAMBER PRESSURE: 35,000 PSI Max

POWDER: Flash Suppressed

PROPELLANT DETECTION: 100% mechanical and/or electronic detection of propellant levels within the cartridges.

VISUAL INSPECTION: 100% both visual and machine vision inspection of finished cartridges prior to packaging.

PACKAGING: Packaged in 50 ct. boxes, 1,000 rounds per case.

MANUFACTURING: Pressure and velocity is tested every 20,000 rounds throughout production to maintain velocity and pressure values. All in-process shots are recorded in the lot summary data packet. CCI – SPEER is ISO 9001:2015 quality certified.

OPERATIONAL STRENGTHS:

- Constructed with the same bonded foundation as standard Gold Dot which virtually eliminates core/jacket separation
- Elastomer filled nose initiates expansion upon impact rather than relying on soft tissue
- No exposed hollow point cavity minimizes probability of bullet plugging in fibrous barriers such as heavy clothing or plywood



www.le.vistaoutdoor.com

[Contact Us](#)

1.14.19